



AQUEOUS
Tempest™ Jet Spray



ENVIRONMENTALLY RESPONSIBLE PRECISION CLEANING

The solution away from solvents

- » Maximize workers' time through automation.
- » Built for years of trouble-free cleaning.
- » No disposal of hazardous or toxic chemicals.
- » Heated, aqueous detergents highly effective on contaminants.
- » Units handle from 1,000 to 50,000 pounds.
- » Custom units engineered to meet specific needs.



Graymills Tempest™ Series Jet Spray Aqueous Parts Washers

INCREASE YOUR IMPACT ON GRIME, REDUCE YOUR IMPACT ON THE ENVIRONMENT



Tempest washers clean with the power of heat and water-based solutions for better results and fewer worries. Gentle on the environment. No toxic fumes, no solvent disposal.



Tempest Premium Front Load

Upgraded features and heavier construction for industrial applications

- » Turntables 25 to 120 inches.
- » Up to 50,000 pound load capacities. Custom load capacities available.
- » V-notch door for loading and unloading access by overhead hoist on 50+ inch turntable.
- » Roll out turntable on models up to and including 42 inch.
- » Stainless steel bushed nozzles.
- » Option-ready shelf allows for upgrades and installation in the field.

AVAILABLE OPTIONS:

- All options
- Oil Skimmer
- Oil Coalescing Systems
- Integrated Rinse and Dry Stages

Tempest Premium Top Load

Compact design for plant location close to work area

- » Turntables 21 to 72 inches.
- » 500 to 2,000 pound load capacities.
- » Strut or hydraulic actuated lid for increased safety and ease of use.
- » Compact design reduces floor space.
- » Stainless steel bushed nozzles.
- » Customizable sizes and options to fit your specific job needs.

AVAILABLE OPTIONS:

- All options
- Oil Coalescing Systems
- Rinse and Blow Off Stages
- Integrated Rinse and Dry Stages





Automated cleaning increases productivity.
Load, set, turn on. Operator can accomplish other tasks while Tempest unit is cleaning parts with powerful jet spray action.



Tempest Parts Washers clean complex parts, large and small.

Cleans Tough Grime

Proper heated water based detergents combined with spray cabinets are effective at cleaning the toughest contaminants.

BUFFING COMPOUND	PAINT
CARBON DEPOSIT	PROCESS FLUID
CORROSION	SALT
GREASE	STAMPING COMPOUND
GRINDING CHIPS	SMUT
GUMMY RESIDUE	VARNISH
LAPPING COMPOUND	WAX
OIL	AND OTHERS

Graymills Tempest Jet Spray Parts Washers are engineered to last.

Standard features and options for All (A), Premium Front Load (P) and Premium Top Load (T):



Non-slip Gear and Sprocket Driven Turntable A

Eliminates the need to replace drive belts, tires or seals.

Reduces maintenance time, component replacement cost.

Breaker protected.



Stainless Steel Oil Skimmer A

Standard on most models, extends life of detergent and assures cleaner parts.



Pressure Nozzles A

Brass or Stainless Steel V-Jet Nozzles.

Durable design with 360° cleaning coverage.



Swing Away Spray Bar A

Nozzle bar swivels for easy loading/unloading clearance.

Better cleaning of small parts with close pressure wash.

Industrial Control Panel A

NEMA rated electrical enclosure featuring IEC components with rotary illuminated cam switches.

Meets NEPA wiring standards for numbering, sizing, color coding, and overload protection.

Vertical Sealless Pump

A Excluding Top Load TL2118

Long-lasting feature, with no seals to leak or replace.

Debris Screen P T

Keeps tank free of larger debris.

Thermostatically Controlled Heating System A

Mechanical door seals P

Eliminate rubberized seal replacement.

Low Water Shut Off

Protect heating element from burnout.

Removable Chip Basket A

Built option ready A

Fabricated and wired for easy installation of options at time of purchase or future on-site upgrades. Options include:

7-day timer for preheat and automatic shutdown.

Automatic water fill.

Two-channel timer to control heater and skimmer.

Steam exhaust system.



cETL Certified to meet stringent requirements of UL-73 (U.S. & Canada). Wired to meet NFPA codes. IEC components (Square D/Allen Bradley) and NEMA Rated control panels on all industrial models.



Graymills Standard Tempest Parts Washer Models

Call for custom quotation on models to meet your specifications.

MODEL	TURNTABLE DIAMETER	WORKING HEIGHT	WEIGHT CAPACITY	TANK CAPACITY	PUMP POWER	STANDARD PUMP OUTPUT	HEATER POWER	TURNTABLE ACCESS
-------	--------------------	----------------	-----------------	---------------	------------	----------------------	--------------	------------------

Tempest Premium Front Load Models | Swing Out Door, Roll Out Turntable

FL2532	25	32	1,000 Lbs.	120 Gal.	3 Hp	52 PSI @ 35 GPM	9 kW	<input checked="" type="checkbox"/> M <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C
FL3136	31	36	1,000 Lbs.	140 Gal.	3 Hp	52 PSI @ 35 GPM	12 kW	<input checked="" type="checkbox"/> M <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C
FL3148	31	48	1,000 Lbs.	140 Gal.	5 Hp	80 PSI @ 85 GPM	12 kW	<input checked="" type="checkbox"/> M <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C
FL3648	36	48	1,500 Lbs.	180 Gal.	5 Hp	80 PSI @ 85 GPM	18 kW	<input checked="" type="checkbox"/> M <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C
FL3660	36	60	1,500 Lbs.	180 Gal.	7.5 Hp	75 PSI @ 120 GPM	18 kW	<input checked="" type="checkbox"/> M <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C
FL4260	42	60	1,500 Lbs.	240 Gal.	7.5 Hp	75 PSI @ 120 GPM	18 kW	<input checked="" type="checkbox"/> M <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C
FL4272	42	72	1,500 Lbs.	240 Gal.	10 Hp	75 PSI @ 150 GPM	36 kW	<input checked="" type="checkbox"/> M <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C

Tempest Premium Front Load Models | V-Notch Door, Fixed Turntable

FL5060	50	60	1,500 Lbs.	300 Gal.	15 Hp	75 PSI @ 200 GPM	36 kW	<input checked="" type="checkbox"/> M <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C
FL5072	50	72	1,500 Lbs.	300 Gal.	15 Hp	75 PSI @ 200 GPM	36 kW	<input checked="" type="checkbox"/> M <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C
FL6060	60	60	1,500 Lbs.	400 Gal.	15 Hp	75 PSI @ 200 GPM	36 kW	<input checked="" type="checkbox"/> M <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C
FL6072	60	72	1,500 Lbs.	400 Gal.	15 Hp	75 PSI @ 200 GPM	36 kW	<input checked="" type="checkbox"/> M <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C
FL7260	72	60	2,000 Lbs.	550 Gal.	15 Hp	75 PSI @ 200 GPM	36 kW	<input checked="" type="checkbox"/> M <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C
FL7272	72	72	2,000 Lbs.	550 Gal.	15 Hp	75 PSI @ 200 GPM	36 kW	<input checked="" type="checkbox"/> M <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C

Tempest Top Load Models | Clamshell door type

TL2524	25	24	1,000 Lbs.	80 Gal.	3 Hp	45 PSI @ 50 GPM	9 kW	<input checked="" type="checkbox"/> M <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C
TL3132	31	32	1,000 Lbs.	125 Gal.	3 Hp	45 PSI @ 50 GPM	13.5 kW	<input checked="" type="checkbox"/> M <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C
TL3636	36	36	1,500 Lbs.	170 Gal.	5 Hp	49 PSI @ 85 GPM	18 kW	<input checked="" type="checkbox"/> M <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C
TL4236	42	36	1,500 Lbs.	220 Gal.	7.5 Hp	74 PSI @ 120 GPM	18 kW	<input checked="" type="checkbox"/> M <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C
TL5036	50	36	1,500 Lbs.	290 Gal.	10 Hp	72 PSI @ 150 GPM	36 kW	<input checked="" type="checkbox"/> M <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C
TL6036	60	36	1,500 Lbs.	390 Gal.	15 Hp	75 PSI @ 200 GPM	36 kW	<input checked="" type="checkbox"/> M <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C
TL7236	72	36	2,000 Lbs.	530 Gal.	15 Hp	75 PSI @ 200 GPM	36 kW	<input checked="" type="checkbox"/> F <input checked="" type="checkbox"/> C

M Manual Loading F Forklift Loading C Overhead Crane Loading

Graymills offers a *Total Cleaning Perspective*, with a complete line of parts washers in varying sizes and cleaning actions. Contact your local distributor or the factory for a catalog or more information. We recommend contacting your representative to set up a **free cleaning analysis** of your exact soils and parts.

No Confusion. No Risk. No Worries.

Graymills products are made in the USA, and are warrantied worldwide.



Graymills Corporation
2601 S. 25th Avenue
Broadview, IL 60155
773-248-6825 phone
773-477-8673 fax

www.graymills.com
info@graymills.com



Contract
Small, Women-Owned Business
#GS-07F-5729P